M12

Circular panel connectors

面板式座子













- 2P, 2+3P, 3P, 4P, 5P, 8P, 12P and 17 poles are available
- Operating voltage: 690V, 630V, 600V, 300V-DC, 250V-AC, 72V-DC, 60V-AC, 48V, 30V,
- Current rating: 16A, 12A, 8A, 4A, 2A, 1.5A
- Mounting type: rear mount (front side fastening the screw), front mount (rear side fastening the screw)
- SUS 316# Stainless steel screw is available



- 2针/孔, 2+3针/孔, 3针/孔, 4针/孔, 5针/孔, 8针/孔, 12针/孔, 17针/孔位可选
- 额定电压:690V, 630V, 600V, 300V-DC, 250V-AC, 72V-DC, 60V-AC, 48V, 30V,
- 额定电流:16A, 12A, 8A, 4A, 2A, 1.5A
- 安装方向:板前装配板后锁紧螺丝、板后装配板前锁紧螺丝
- 可选316不锈钢螺丝



M12 D-Code male panel connector, EMI-Shielded, with cable



M12 D-Code female panel connector, EMI-Shielded, with cable



M12 4Pin D-Code nanel mount connector to R I45 male plug with Cat 5e S/FTP 2x2x22AWG Ethernet cable



M12 A-Code male panel connector, front side fastening, Plastic Screw, with single wires



M12 A-Code female panel connector, front side fastening, Plastic Screw, with single wires



M12 X-Code female panel connector, front side fastening, PCB Contacts, with 90 degree PCB contacts



PG9 Chassis-side M12 male-female in one through wall type panel connector



M12 A-Code male square flange type panel connector, customized solution, end with IDC connectors



M12 A-Code 8Pin male panel connector, rear side fastening, end with JST ZHR board connectors



M12 D-Code male panel connector, EMI-Shielded, molded with cable



M12 D-Code female panel connector, EMI-Shielded, molded with cable

